

# Cold Shot Chillers®



**RUGGED  
DEPENDABILITY**

## 2 through 10-Ton Air-Cooled Portable Single Stage Water Chillers



(7.5 TON UNIT SHOWN)

### FEATURES

- Dependable Copeland Welded Hermetic Scroll Compressors
- Stainless Steel Brazed Plate Evaporators Vacuum Brazed with Copper
- External Brass Service Valves
- Large Copper Condensing Coil with Aluminum Fins
- Powder Coated, Louvered Protective Condenser Panels
- Strong Stainless Steel Centrifugal Pumps with Safety Fuses or Thermal Protection
- Oversized Magnetic Contactors
- Powder Coated Steel Frame and Welded Stainless Steel Reservoir

### BENEFITS

- Long Life - Maintenance Free
- Compact Efficiency
- Allows for Field Service Without Disassembly
- Easy Maintenance - Improved Efficiency
- Rugged Protection While Allowing for Easy Maintenance and Wash Down
- High Flow - Long Life - Dependable
- Rugged Dependability - Long Life
- Lifetime Warranty



## TECHNICAL SPECIFICATIONS

CAPACITY ± 5% AT 50°F LCWT/ 95° AMBIENT	2 -TON 24,000 BTU/HR	3 -TON 36,000 BTU/HR	5 -TON 60,000 BTU/HR	7.5 -TON 90,000 BTU/HR	10 -TON 120,000 BTU/HR
MODEL	ACWC-24-E	ACWC-36-E	ACWC-60-E	ACWC-90-E	ACWC-120-D
VOLTAGE/PHASE	208/230/1	208/230/3* 480/3	208/230/3* 480/3	208/230/3 480/3	208/230/3 480/3
MINIMUM CIRCUIT AMPS	27	18 11	27 15	36 17	50 23
DIMENSIONS (APPROX.)	38" L x 28" W x 48" H	44" L x 32" W x 56" H	44" L x 32" W x 60" H	44" L x 32" W x 60" H	50" L x 40" W x 69" H
WEIGHT	350 LBS	390 LBS	500 LBS	890 LBS	906 LBS
PUMP	1 HP	1 HP	1 HP	1-1/2 HP	1-1/2 HP
PUMP OUTPUT	30 GPM @ 30PSI	30 GPM @ 30PSI	30 GPM @ 30PSI	55 GPM @ 30PSI	55 GPM @ 30PSI
TANK SIZE	25 GAL	25 GAL	25 GAL	41 GAL	41 GAL
FLUID CONNECTIONS (IN/OUT)	1" MNPT	1" MNPT	1" MNPT	1-1/4" MNPT	1-1/4" MNPT
TANK CONSTRUCTION	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL

\* 208/230 volt 1 phase units available

### CONTROLS:

Electronic temperature controller with constant (set point/process temperature) LED readout on standard units.

### REFRIGERATION COMPONENTS:

Efficient scroll compressors, sight glass/moisture indicators, balanced port expansion valves, filter driers, service valves, stainless steel/copper brazed plate evaporators, fan cycling head pressure controls.

### PROCESS FLUID COMPONENTS:

Rugged stainless steel centrifugal pumps, with manual by-pass, bronze "Y" strainer with 20 mesh stainless steel screen, insulated stainless steel reservoir with shoe box lid, tank level sights glass, fill and drain ports.

### SAFETY CONTROLS:

High/low pressure safety, freeze, low water flow safety with manual reset, internal overloads, thermal overloads or safety fuses for pumps and fan motors.

### OPERATING TEMPERATURES:

Process fluid: 42°F to 70°F for standard units (20°F to 70°F for low leaving fluid temperature units)

Ambient air: 40°F to 115° for standard units (-20°F to 115°F for outdoor units with optional low ambient modifications)

### CONSTRUCTION:

All welded powder coated steel frame and cabinet, 5" Phenolic casters with ball bearings and grease fittings (On Indoor Models add 6 1/2" to height)

### WARRANTY:

One Year Parts; Five Year Compressor

## OPTIONS

- Flow Capacities (Pump Up-Grade)
- Outdoor Service
- Low Leaving Fluid Temperature
- Spare Parts Kit
- Labor Warranty
- Split System
- Reverse-Flow
- Hot Gas By-Pass For Capacity Control
- Multiple Pumps
- EZ Clean Filter
- Low Ambient Modification
- Line Phase Monitor Protection
- Flow Meters
- Pro-Tec Coil Coating

Note: All specifications subject to change without notice.

**Compare our Price and Warranty**

2730 Maximilian Dr., Houston, Texas 77032 • 281-227-8400 t • 1-800-473-9178 toll free • 281-227-8404 f  
www.waterchillers.com